



## Breeze™ Mini BTE

AGCo

Trimmer Controlled, Quiet Mode Expansion


### HEARING AID FEATURES

- Digital sound processing for clear, comfortable sound
- Output compression limiting
- Two controls provide fitting flexibility
  - L - Low-cut (green)
  - P - Maximum power output (blue)
- Controls continuously adjustable in steps for precise adjustment
- Quiet mode expansion for improved sound quality in quiet environment and reduced circuit noise
- Power management system provides optimized battery life
- Low battery warning
- Volume control: numbered 1 (low) to 4 (high)
- Unfiltered earhook
- Battery size 13

### OPTIONS

- Tamper-resistant volume control
- Tamper-resistant battery door

### SUITABLE FOR FITTING MODERATE TO SEVERE HEARING LOSSES




Fitting Guide

Can fit audiogram configurations ranging from flat to sloping.


### ANSI 3.22-1996 TECHNICAL DATA

Frequency Range	200-4900 Hz	
Peak Gain	65 dB	
Peak Output	130 dB	
Reference Test Gain	47 dB	
HF Average Gain	61 dB	
HF Average OSPL90	124 dB	
Typical Battery Life (Zinc Air Premium)	260 h	
Current Drain at RTP	1.1 mA	
Equivalent Input Noise at RTP	20 dB	
Total Harmonic Distorsion at RTP		
500 Hz	typical 3%	< 5%
800 Hz	typical 1%	< 3%
1600 Hz	typical 1%	< 3%
Attack Time	< 10 ms	
Release Time	80 ms	
Compression Ratio	∞:1	


# BREEZE AGCo DIGITAL MINI BTE ANSI SPECIFICATIONS




Input sound pressure level: 90 dB  
Volume Control: full on



Input sound pressure level: 50 dB  
Volume Control: RTP



Input sound pressure level: 50 dB  
Volume Control: as shown



Input at 2000 Hz  
Volume Control: as shown

## TEST CONDITIONS

RTP-ANSI: Reference Test Position of the Volume Control: 3.1  
 BATTERY: 13 Zinc Air Premium  
 SOURCE: Voltage 1.3 V  
 Impedance 6 Ohms  
 EARHOOK: Unfiltered  
 TUBING: Length 25 mm,  
 Inside Diameter 1.93 mm  
 Refer to: "Summary of Test Conditions and Limits" for more details.

## AID MARKING: Breeze AGCo

## COMPLIANCE

Our products are designed to meet all of the limits required when tested in accordance with the applicable standard.

## REFERENCES

ASA: Acoustical Society of America, ANSI S3.22-1996  
 FDA: Food and Drug Administration, Part 801

We reserve the right to change specification data without notice as improvements are introduced.

This product is manufactured under the protection of U.S. Patent #4349082 & #5204917.

Caution: Hearing aids and batteries can be harmful if swallowed or improperly used.

Sound pressure level of this hearing aid exceeds 132 dB SPL.



**CORPORATE OFFICE**  
 Kitchener, Ontario, Canada  
 877 492 6244; 519 895 0100

**CANADA**  
 Cambridge, Ontario  
 800 265 8255; 519 650 9111

**EUROPE**  
 Bremen, Germany  
 49 421 43 87 90

**FRANCE**  
 Bron, France  
 04 26 23 22 00

**INTERNATIONAL**  
 Kitchener, Ontario, Canada  
 519 895 0100

**NETHERLANDS**  
 Nieuwegein, The Netherlands  
 +31 (0) 30 604 9325

**UK**  
 Warrington, Cheshire, England  
 01925 247810

**U.S.A.**  
 Plymouth, Minnesota  
 800 888 8882; 763 744 3300

www.unitronhearing.com