

Programmable



Sound F/X Pro Mini-BTE

Multi-Channel Wide Dynamic Range Compression


HEARING AID FEATURES

- Two channels with Wide Dynamic Range Compression circuitry that is independently adjustable for each channel
- Five parameters provide extensive fitting flexibility:
 - GL – Low-channel Gain
 - GH – High-channel Gain
 - F – Crossover Frequency
 - TK – Threshold Kneepoint
 - P – Power
- Class D circuitry for excellent battery life
- Slim mini-housing
- Maximum Power Output tied to Volume Control
- Volume Control: numbered 1 (low) to 4 (high)
- O-T-M Switch: 3 positions Off–Telecoil–Microphone
- Direct Audio Input - MLx compatible
- Two-tone, beige/taupe housing
- Filtered earhook
- Battery size: 13
- Sound F/X can be programmed using NOAH-compatible Unifit, Standalone Unifit or portable Pocket Unifit software

OPTIONS

- O-T-MT-M Switch: 4 positions
Off–Telecoil–Microphone/Telecoil–Microphone
- O-MT-M Switch: 3 positions Off–Microphone/Telecoil–Microphone
- Tamper-resistant battery compartment/Volume Control cover
- CROS/BiCROS
- Child-sized earhook
- Sideplate colours: opaque taupe, brown and grey; transparent red, green and blue; fluorescent pink and yellow

SUITABLE FOR FITTING MILD TO MODERATELY SEVERE HEARING LOSSES



IEC 118-0 TECHNICAL DATA


Frequency Range	100-8000 Hz
Peak Gain (40 dB in)	66 dB
Peak Output	124 dB
Reference Test Gain	43 dB
Full on Average Gain*	56 dB
Average Output*	118 dB
Reference Test Frequency	1.6 kHz
Full on Gain at 1.6 kHz (50 dB in)	58 dB
Output at 1.6 kHz	125 dB
Typical Battery Life (Zinc Air Premium)	260 h
Current Drain at RTG	< 0.9 mA
Output with Inductive Input at 1.6 kHz	89 dB
Equivalent Input Noise at RTG (40 dB in)	< 28 dB typical 24 dB
Fast Time Constant	
Attack Time	5 ms
Release Time	20 ms
Slow Time Constant	
Attack Time	200 ms
Release Time	400 ms
Compression Ratio	4:1 to 1:1

*Average of 500, 1000 and 2000 Hz


IEC 118-7 2cc COUPLER

Frequency Range	100-8000 Hz
Peak Gain (40 dB in)	56 dB
Peak Output	116 dB
Reference Test Gain	35 dB
Full on Gain at 1.6 kHz	49 dB
Output at 1.6 kHz	110 dB


SOUND F/X PROGRAMMABLE MINI-BTE IEC 118-o EAR SIMULATOR




Input sound pressure level: 90 dB
Volume Control: full on
GL + GH + F - TK - P +




Input sound pressure level: 60 dB
Volume Control: RTG
GH + F + TK - P +




Input sound pressure level: 60 dB
Volume Control: RTG
GL + F - TK - P +




Input sound pressure level: 60 dB
Volume Control: RTG
GL +/- GH +/- TK - P +




Input at 1600 Hz
Volume Control: full on
GL + GH + F - P +




Input sound pressure level: 100 dB
Volume Control: full on
GL + GH + F - TK -




Input at 1600 Hz
Volume Control: as shown
GL + GH + F - TK - P +



Input sound pressure level: 50 dB
Volume Control: as shown
GL + GH + F - TK - P +




Input sound pressure level: 60 dB
Volume Control: RTG
"A" unfiltered, not recommended
"B" filtered, standard




Input: 1 mA/m
Volume Control: full on
GL + GH + F - TK - P +

IEC 118 -7 2cc COUPLER



Input sound pressure level: 90 dB
Volume Control: full on
GL + GH + F - TK - P +



Input sound pressure level: 60 dB
Volume Control: RTG
GL +/- GH +/- TK - P +

TEST CONDITIONS

RTG-IEC: Reference Test Gain of the Volume Control: 3.5
BATTERY: 13 Zinc Air Premium
SOURCE: Voltage 1.3 V Impedance 6 Ohms
EARHOOK: Filtered
TUBING: Length 25 mm, Inside Diameter 1.93 mm
Refer to: "Summary of Test Conditions and Limits" for more details.

AID MARKING: S F/X Pro

COMPLIANCE

Our products are designed to meet all of the limits required when tested in accordance with the applicable standard.

REFERENCES

IEC: International Electrotechnical Commission Publication 118-o, 118-7 (1994)
European Standard EN60118/A1 February, 1994
DIN: Deutsche Normen DIN 45 605 (1986)
JIS: Japanese Industrial Standard JIS C 5512-2000

We reserve the right to change specification data without notice as improvements are introduced.

This product is manufactured under the protection of U.S. Patent #4349082 & #5204917.

Caution: Hearing aids and batteries can be harmful if swallowed or improperly used.



CORPORATE OFFICE

Kitchener, Ontario, Canada
877 492 6244; 519 895 0100
fax 519 895 0108

CANADA

Cambridge, Ontario
800 265 8255; 519 650 9111
fax 800 949 6663

U.S.A.

Plymouth, Minnesota
800 888 8882; 763 744 3300
fax 763 557 8828

INTERNATIONAL

Kitchener, Ontario, Canada
519 895 0100
fax 519 895 2318

EUROPE

Bremen, Germany
49 421 43 87 90
fax 49 421 48 81 56

www.unitronhearing.com