

## Next™ 16 BTE Series

AutoPro3™




16 Channels, 16 Bands, Adaptive Directionality

### HEARING INSTRUMENT FEATURES

- AutoPro3™ offers faster detection and response of the 3 listening destinations and the ability to adjust comfort and clarity in all destinations
- Highly advanced feedback management that delivers more usable gain, allowing clients to enjoy the natural comforts and advantages of an open fit
- Comfort-Clarity Balance gives the client control of adaptive features (speech enhancement and noise reduction)
- AntiShock™ instantaneously reduces the level of impulse noises such as a door slam, while maintaining the quality and intelligibility of speech
- Speech enhancement LD emphasizes speech signals based on the input level
- 16 channels provide high resolution signal processing
- Adaptive directional microphone system tracks and suppresses moving noise sources, while focusing on sounds from the front
- Noise Reduction, Wind Noise Manager
- Data logging accurately records data on time spent in each program and listening destination. Volume control and Comfort-Clarity Balance changes are also logged in manual and automatic programs.
- MyMusic™ enhances the music listening experience by bringing out the rich, full tones of music
- OnBoard™ control is easily configured as a volume control or program button
- Easy-t provides automatic switching to a dedicated telephone program
- Ideal volume indicator provides a beep notification when preferred gain is reached on the volume control
- Digital volume control lever for easy control with reduced dexterity
- Up to 3 additional manual programs provide customization for individual needs and preferences
- Easy-DAI provides automatic switching to a dedicated DAI program
- Low battery warning
- Start up delay
- On/Off by opening or closing the battery door
- Can be programmed using NOAH-compatible U:fit™ and Standalone U:fit fitting software v1.4 or higher
- Choice of processing strategy, WDRC or Linear Limiting
- Battery Size: 13

### OPTIONS & ACCESSORIES






- Remote control with volume control, Comfort-Clarity Balance, program change button, and more
- Tamper-resistant volume control
- Tamper-resistant battery door
- Filtered earhook
- Slim tube coupling for instant open fittings (on Next 16, 125/60 model only)
- Choice of shell colours
- Direct Audio Input unit



Next 16 is suitable for fitting mild to severe hearing losses and can fit audiogram configurations ranging from reverse to precipitously sloping.

# Next 16 BTE Series

ANSI S3.22-1996 / IEC 118-7 2CC COUPLER TECHNICAL DATA		ANSI S3.22-1996 / IEC 118-7 2CC COUPLER TECHNICAL DATA		IEC 118-0 OES COUPLER TECHNICAL DATA			
Reference Test Frequency ANSI IEC 118-7	Next 16 Slim Tube (optional)	Next 16 (power)	Next 16 HP (high power)	Reference Test Frequency IEC 118-0	Next 16 Slim Tube (optional)	Next 16 (power)	Next 16 HP (high power)
<b>OSPL90</b> Maximum HFA at RTF	HFA 2.5 kHz	HFA 1.6 kHz	HFA 1.6 kHz	<b>OSPL90</b> Maximum at RTF	1.6 kHz	1.6 kHz	1.6 kHz
<b>Full on Gain</b> (input 50 dB) Maximum HFA at RTF	124 dB 108 dB 109 dB	125 dB 122 dB 121 dB	130 dB 125 dB 123 dB	<b>Full on Gain</b> (input 50 dB) Maximum at RTF	58 dB 46 dB	63 dB 59 dB	73 dB 64 dB
<b>Basic Frequency Response</b> Frequency Range (Hz) Reference Test Gain (ANSI 1996)	100-6300 30 dB	100-5900 45 dB	100-5600 48 dB	<b>Basic Frequency Response</b> Frequency Range in Hz (DIN) Reference Test Gain	100- 5700 39 dB	100- 6200 51 dB	100- 5800 55 dB
<b>Induction Coil Sensitivity</b> (ANSI 1996, 31.6 mA/m) HFA SPLITS STS	89 dB -1 dB	104 dB -1 dB	108 dB 0 dB	<b>Induction Coil Sensitivity</b> Graph shown for 31.6 mA/m at RTG at RTF (1 mA/m at Full On Gain) Maximum at RTF	99 dB 86 dB 77 dB	111 dB 90 dB 88 dB	115 dB 100 dB 93 dB
<b>Current Drain at RTG</b>	1.1 mA	1.2 mA	1.7 mA	<b>Current Drain at RTG</b>	1.1 mA	1.1 mA	1.3 mA
<b>Typical Battery Life</b>	265 h	245 h	170 h	<b>Typical Battery Life</b>	265 h	265 h	205 h
<b>Equivalent Input Noise at RTG</b>	28 dB	20 dB	20 dB	<b>Equivalent Input Noise at RTG</b>	28 dB	20 dB	20 dB
<b>Total Harmonic Distortion</b> at 500 Hz at 800 Hz at 1600 Hz	1% 1% 1%	4% 2% 1%	1% 1% 1%	<b>Total Harmonic Distortion</b> at 500 Hz at 800 Hz at 1600 Hz	2% 2% 1%	3% 2% 2%	2% 2% 2%
<b>EMC immunity by ANSI C63.19-2001 EMC, Low Band and High Band Omni mode/Telecoil</b>	M4/T4	M4/T4	M3/T4	<b>EMC immunity by IEC 118-13, Field Strength 75/50 V/m, Omni mode</b>	39/48	39/48	40/51
				<b>IRIL Low/High band dB SPL</b>			40/51



### Test Conditions:

Battery: 13  
Source: Voltage 1.3 V  
Earhook: Unfiltered  
Tubing: Length 25 mm; Inside Diameter 1.93 mm  
The measurement data obtained with hearing instrument set to omni mode with all adaptive features disabled.

Domes should never be fitted on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend to use a customized ear mold. Sound pressure level of this hearing aid exceeds 132 dB SPL. We reserve the right to change specification data without notice as improvements are introduced.

